

WOOD HERRINGBONE

ISOCORE 6.5

10 YEAR GUARANTEE COMMERCIAL

25 YEAR GUARANTEE DOMESTIC



ISOCORE 6.5 / IC11165433

HERRINGBONE NATURAL



ISOCORE 6.5 / IC1116522502

HERRINGBONE CLASSIC



ISOCORE 6.5 / IC1116522509

HERRINGBONE BROWN

ISOCORE CLASSIC, WIDE & HERRINGBONE

CONSTRUCTION / CONSTRUCTION / COSTRUZIONE / CONSTRUCTIE / KONSTRUKTION / CONSTRUCCIÓN

TOTAL THICKNESS / ÉPAISSEUR TOTALE / SPESSORE / TOTALE DIKTE / TOTAL DICKE / ESPESOR

WEAR LAYER / COUCHE D'USURE / STRATO D'USURA / SLIJTLAG / NUTZSCHICHT / CAPA DE USO

UTILIZATION CLASS / CLASSE D'USAGE / CLASSE D'UTILIZZO / GEBRUIKERSKLASSE / STRAPAZIENKLASSE / CLASSE DE UTILIZACIÓN

COATING / PROTECTION / RIVESTIMENTO / BESCHERMING / BESCHICHTUNG / REVESTIMIENTO

EMBOSSING / STRUCTURE / STRUTTURA / STRUCTUUR / STRUKTUR / RELIEF

BEVELLED / BISEAUTÉ / BISELLATURA / V-GROEF / ABGESCHRÄGT / BISELADO

PLANK SIZE / DIMENSIONS DE LA LAME / DIMENSIONI / AFMETING PER PANEEL / ABMESSUNG DER DIELEN / TAMAÑO DE LAMA

CARTON PACKING / EMBALLAGES EN CARTON / SCATOLE / KARTONNEN VERPAKKING / KARTONVERPACKUNG / EMBALAJE DE CARTÓN

PALLET PACKING / BÔTES PAR PALETTE / NIR SCATOLE A PALETTA / DOZEN PER PALLET / VERPACKUNG AUF PALETTE / EMBALAJE DE PALÉ

IMPACT SOUND REDUCTION / RÉDUCTION DU BRUIT D'IMPACT / RIDUZIONE DEL RUMORE DA CALPESTIO / IMPACT GELUIDVERMINDERING / AUSWIRKUNG KLANG REDUCTION / REDUCCION DEL IMPACTO SONORO

CASTOR CHAIR RESISTANCE / ESSAI DE LA CHAISE À ROULETTES / PROVA CON POLTRANA A ROTELLE / ROLWEERSTAND BUREAUSTOEL / STUHLROLLENWIDERSTAND / RESISTENCIA A LA RUEDA DE LAS SILLAS

MICRO-SCRATCH RESISTANCE / RÉSISTANCE AUX MICRO-RAYURES / RESISTENZA AI MICRO-GRAFFI / MICRO-KRASBESTÄNDIGHEIT / MIKROKRATZWIDERSTAND / RESISTENCIA A MICRO-RASGUÑOS

ELECTROSTATIC PERFORMANCE / POTENTIEL DE CHARGE ELECTROSTATIQUE / POTENZIALE DI CRICALETTROSTATICA / ELECTROSTATISCHE EIGENSCHAPPEN / ELEKTROSTATISCHE EIGENSCHAFT / RENDIMIENTO ELECTROSTATICO

SLIP RESISTANCE / ANTIDÉPARANT / RESISTENZA ALLO SCIVOLAMENTO / SLIPWEERSTAND / RUTSCHFESTIGKEIT / RESISTENCIA AL DESLIZAMIENTO

WEAR RESISTANCE / RÉSISTANCE D'USURE / RESISTENZA ALL'USURA / SLIJTVASTHEID / VERSCHLEISSBESTÄNDIGKEIT / RESISTANCIA AL DESGASTE

RESIDUAL INDENTATION / POINÇONNEMENT RÉMANENT / SENSIBILITÀ DI IMPRESSIONE / INDRUNGEVOELHEID / RESTEINDRUCK / MARGEN RESIDUAL

DIMENSIONAL STABILITY / STABILITÉ DIMENSIONELLE / STABILITÀ DIMENSIONALE / DIMENSIONALE STABILITEIT / DIMENSIONENSTABILITÄT / ESTABILIDAD DIMENSIONAL

FIRE RATING / CLASSIFICATION AU FEU / CLASSIFICAZIONE AL FUOCO / BRANDKLASSE / BRANDKLASSE / CLASSIFICACIÓN DE RESISTENCIA AL FUEGO

FORMALDEHYDE EMISSION / EMISSION DE FORMALDEHYDE / EMISSIONE DI FORMALDEIDE / FORMALDEHYDE EMISSIE / FORMALDEHYD-EMISSION / EMISIÓN DE FORMALDEHIDO

THERMAL RESISTANCE / RÉSISTANCE THERMIQUE / RESISTENZA TERMICA / THERMISCHE WEERSTAND / WÄRMEBESTÄNDIGKEIT / RESISTENCIA TERMICA

WARRANTY FOR DOMESTIC USE / PÉRIODE DE GARANTIE USAGE DOMESTIQUE / GARANZIA PER USO DOMESTICO / GARANTIEPERIODE HUISHOUDELIJK GEBRUIK / GARANTIE FÜR PRIVATEGEBRAUCH / GARANTÍA PARA USO DOMÉSTICO

WARRANTY FOR COMMERCIAL USE / PÉRIODE DE GARANTIE USAGE COMMERCIAL / GARANZIA PER USO COMMERCIALE / GARANTIEPERIODE COMMERCIEEL GEBRUIK / GARANTIE FÜR KOMMERZIELLEN GEBRAUCH / GARANTÍA PARA USO COMMERCIAL

	ISOCORE CLASSIC	ISOCORE WIDE	ISOCORE HERRINGBONE
CONSTRUCTION / CONSTRUCTION / COSTRUZIONE / CONSTRUCTIE / KONSTRUKTION / CONSTRUCCIÓN	1.5 MM LVT + 4 MM ISOCORE + 1 MM IXPE PAD	1.5 MM LVT + 4 MM ISOCORE + 1 MM IXPE PAD	1.5 MM LVT + 4 MM ISOCORE + 1 MM IXPE PAD
TOTAL THICKNESS / ÉPAISSEUR TOTALE / SPESSORE / TOTALE DIKTE / TOTAL DICKE / ESPESOR	6.5 MM	6.5 MM	6.5 MM
WEAR LAYER / COUCHE D'USURE / STRATO D'USURA / SLIJTLAG / NUTZSCHICHT / CAPA DE USO	0.55 MM	0.55 MM	0.55 MM
UTILIZATION CLASS / CLASSE D'USAGE / CLASSE D'UTILIZZO / GEBRUIKERSKLASSE / STRAPAZIENKLASSE / CLASSE DE UTILIZACIÓN	EN 16911 CLASS 34	CLASS 34	CLASS 34
COATING / PROTECTION / RIVESTIMENTO / BESCHERMING / BESCHICHTUNG / REVESTIMIENTO	ANTIBACTERIAL ANTISCRATCH CERAMIC BEAD PU	ANTIBACTERIAL ANTISCRATCH CERAMIC BEAD PU	ANTIBACTERIAL ANTISCRATCH CERAMIC BEAD PU
EMBOSSING / STRUCTURE / STRUTTURA / STRUCTUUR / STRUKTUR / RELIEF	TRU-WOOD	TRU-WOOD	TRU-WOOD
BEVELLED / BISEAUTÉ / BISELLATURA / V-GROEF / ABGESCHRÄGT / BISELADO	YES	YES	YES
PLANK SIZE / DIMENSIONS DE LA LAME / DIMENSIONI / AFMETING PER PANEEL / ABMESSUNG DER DIELEN / TAMAÑO DE LAMA	190 X 1210 MM	220 X 1210 MM	120 X 720 MM
CARTON PACKING / EMBALLAGES EN CARTON / SCATOLE / KARTONNEN VERPAKKING / KARTONVERPACKUNG / EMBALAJE DE CARTÓN	1.84 M ² 8 PLANKS	1.86 M ² 7 PLANKS	2.07 M ² 24 PLANKS
PALLET PACKING / BÔTES PAR PALETTE / NIR SCATOLE A PALETTA / DOZEN PER PALLET / VERPACKUNG AUF PALETTE / EMBALAJE DE PALÉ	73.60 M ² 40 CARTONS	81.84 M ² 44 CARTONS	81.84 M ² 40 CARTONS
IMPACT SOUND REDUCTION / RÉDUCTION DU BRUIT D'IMPACT / RIDUZIONE DEL RUMORE DA CALPESTIO / IMPACT GELUIDVERMINDERING / AUSWIRKUNG KLANG REDUCTION / REDUCCION DEL IMPACTO SONORO	EN ISO 717-2 19 dB	19 dB	19 dB
CASTOR CHAIR RESISTANCE / ESSAI DE LA CHAISE À ROULETTES / PROVA CON POLTRANA A ROTELLE / ROLWEERSTAND BUREAUSTOEL / STUHLROLLENWIDERSTAND / RESISTENCIA A LA RUEDA DE LAS SILLAS	EN ISO 4910 - EN 425 RATING: 5.0 NO CHANGE	RATING: 5.0 NO CHANGE	RATING: 5.0 NO CHANGE
MICRO-SCRATCH RESISTANCE / RÉSISTANCE AUX MICRO-RAYURES / RESISTENZA AI MICRO-GRAFFI / MICRO-KRASBESTÄNDIGHEIT / MIKROKRATZWIDERSTAND / RESISTENCIA A MICRO-RASGUÑOS	EN 16094 MSR-A2 MSR-B2	MSR-A2 MSR-B2	MSR-A2 MSR-B2
ELECTROSTATIC PERFORMANCE / POTENTIEL DE CHARGE ELECTROSTATIQUE / POTENZIALE DI CRICALETTROSTATICA / ELECTROSTATISCHE EIGENSCHAPPEN / ELEKTROSTATISCHE EIGENSCHAFT / RENDIMIENTO ELECTROSTATICO	EN 1815 < 2 KV	< 2 KV	< 2 KV
SLIP RESISTANCE / ANTIDÉPARANT / RESISTENZA ALLO SCIVOLAMENTO / SLIPWEERSTAND / RUTSCHFESTIGKEIT / RESISTENCIA AL DESLIZAMIENTO	DIN 51130 R10	R10	R10
WEAR RESISTANCE / RÉSISTANCE D'USURE / RESISTENZA ALL'USURA / SLIJTVASTHEID / VERSCHLEISSBESTÄNDIGKEIT / RESISTANCIA AL DESGASTE	EN 660-2 >4000 CYCLES	>4000 CYCLES	>4000 CYCLES
RESIDUAL INDENTATION / POINÇONNEMENT RÉMANENT / SENSIBILITÀ DI IMPRESSIONE / INDRUNGEVOELHEID / RESTEINDRUCK / MARGEN RESIDUAL	EN ISO 24343-1 < 0.10 MM	< 0.10 MM	< 0.10 MM
DIMENSIONAL STABILITY / STABILITÉ DIMENSIONELLE / STABILITÀ DIMENSIONALE / DIMENSIONALE STABILITEIT / DIMENSIONENSTABILITÄT / ESTABILIDAD DIMENSIONAL	EN 434 < 0.10%	< 0.10%	< 0.10%
FIRE RATING / CLASSIFICATION AU FEU / CLASSIFICAZIONE AL FUOCO / BRANDKLASSE / BRANDKLASSE / CLASSIFICACIÓN DE RESISTENCIA AL FUEGO	EN ISO 9239-1 BFL-S1	BFL-S1	BFL-S1
FORMALDEHYDE EMISSION / EMISSION DE FORMALDEHYDE / EMISSIONE DI FORMALDEIDE / FORMALDEHYDE EMISSIE / FORMALDEHYD-EMISSION / EMISIÓN DE FORMALDEHIDO	EN 1717-1 CLASS E1	CLASS E1	CLASS E1
THERMAL RESISTANCE / RÉSISTANCE THERMIQUE / RESISTENZA TERMICA / THERMISCHE WEERSTAND / WÄRMEBESTÄNDIGKEIT / RESISTENCIA TERMICA	EN ISO 12524 0.0621 m ² K/W	0.0621 m ² K/W	0.0621 m ² K/W
WARRANTY FOR DOMESTIC USE / PÉRIODE DE GARANTIE USAGE DOMESTIQUE / GARANZIA PER USO DOMESTICO / GARANTIEPERIODE HUISHOUDELIJK GEBRUIK / GARANTIE FÜR PRIVATEGEBRAUCH / GARANTÍA PARA USO DOMÉSTICO	25 YEARS	25 YEARS	25 YEARS
WARRANTY FOR COMMERCIAL USE / PÉRIODE DE GARANTIE USAGE COMMERCIAL / GARANZIA PER USO COMMERCIALE / GARANTIEPERIODE COMMERCIEEL GEBRUIK / GARANTIE FÜR KOMMERZIELLEN GEBRAUCH / GARANTÍA PARA USO COMMERCIAL	10 YEARS	10 YEARS	10 YEARS

ISOCORE WOOD I

ISOCORE WOOD I

ISOCORE 6,5 PLANK WIDE 220 X 1210
ISOCORE 6,5 PLANK CLASSIC 190 X 1210
ISOCORE 6.5 PLANK HERRINGBONE 120 x 720



LUXURY VINYL FLOORING



WOOD HERRINGBONE

ISOCORE 6.5

10 YEAR GUARANTEE COMMERCIAL

25 YEAR GUARANTEE DOMESTIC



ISOCORE 6.5 / IC1116522506

HERRINGBONE GREY



ISOCORE CLICK BACKSIDE

ISOCORE CLICK




- SUPERIOR CASTOR CHAIR PERFORMANCE
- CAN BE INSTALLED IN OFFICES WITH CASTOR CHAIRS

FR - TRÈS BONNE RÉSISTANCE AU PASSAGE DES CHAISES À ROULETTES
IT - PERFORMANCE SUPERIORE PER SEDIE CON RUOTE
NL - ZEER GOEDE WEERSTAND BIJ STOELN MET WIELTJES
DE - HERVORRAGENDE STUHLROLLENGEIGNUNG
ES - EXCELENTE CONFORT. MÁS LIGERA.

- ENHANCED WALKING SOUND ISOLATION
- EXCELLENT COMFORT & LIGHTER WEIGHT

FR - AMÉLIORE LES BRUITS CAUSÉS PAR LES PAS
IT - ISOLAMENTO ACUSTICO AL CALPESTIO MIGLIORATO
NL - VERHOOGDE GELUIDSDEMPING
DE - VERBESSERTE GEHSCHALLDÄMMUNG
ES - PUEDE INSTALARSE EN OFICINAS DONDE SE USEN SILLAS CON RUEDAS

FR - PEUT ÊTRE INSTALLÉ DANS LES BUREAUX ÉQUIPÉS DE CHAISES À ROULETTES
IT - PUÒ ESSERE INSTALLATO IN UFFICI CON SEDIE CON RUOTE
NL - KAN GEÏNSTALLEERD WORDEN IN KANTOREN MET BUREAUSTOELN OP WIELTJES
DE - KANN IN BÜROS MIT STUHLROLLEN INSTALLIERT WERDEN
ES - RENDIMIENTO SUPERIOR CON EL USO DE SILLA CON RUEDAS



WOOD CLASSIC

ISOCORE 6.5

10 YEAR GUARANTEE COMMERCIAL 25 YEAR GUARANTEE DOMESTIC



ISOCORE 6.5 / IC978108

AMSTERDAM OAK GREY



ISOCORE 6.5 / IC978102

AMSTERDAM OAK WHITE



ISOCORE 6.5 / IC725110

CALHOUN OAK

WOOD WIDE

ISOCORE 6.5



ISOCORE 6.5 / IC967112

GOLDEN OAK ARCTIC



ISOCORE 6.5 / IC967115

GOLDEN OAK WHITE



ISOCORE 6.5 / IC967116

GOLDEN OAK WHEAT



ISOCORE 6.5 / IC2236524813

WARM OAK LIGHT



ISOCORE 6.5 / IC2236524802

WARM OAK NATURAL



ISOCORE 6.5 / IC22365245

NATURAL OILED OAK

10 YEAR GUARANTEE COMMERCIAL 25 YEAR GUARANTEE DOMESTIC



ISOCORE 6.5 / IC2236524815

SANDED OAK LIGHT



ISOCORE 6.5 / IC966107

SMOKED OAK CAPRICE



ISOCORE 6.5 / IC967113

GOLDEN OAK BROWN