

CLICK STONE / CARRE



ISOCORE 7.5 / IC1176532806

CREA SQUARE GREY

Featuring  **ISOCORE** Technology™



ISOCORE 8.0 / IC1176532910

LAGRIMA SQUARE LIGHT



ISOCORE 8.0 / IC1176532912

LAGRIMA SQUARE DARK

CLICK STONE / CARRE



ISOCORE 7.5 / IC1176532706

MELAN SQUARE GREY

Featuring  ISOCORE Technology™



ISOCORE 7.5 / IC1176532714

MELAN SQUARE WHITE



ISOCORE 7.5 / IC1176532710

MELAN SQUARE LIGHT

CLICK STONE / CARRE



ISOCORE 7.5 / IC1176532606

MYKONOS SQUARE MEDIUM GREY

Featuring  **ISOCORE** Technology™



ISOCORE 7.5 / IC1176532712

MELAN SQUARE BEIGE




ISOCORE 7.5 / IC1176532611

MYKONOS SQUARE FLAMED

CLICK STONE / CARRE




ISOCORE 7.5 / **ICI176532806**
CREA SQUARE GREY



ISOCORE 8.0 / **ICI176532910**
LAGRIMA SQUARE LIGHT



ISOCORE 8.0 / **ICI176532912**
LAGRIMA SQUARE DARK



ISOCORE 7.5 / **ICI176532706**
MELAN SQUARE GREY



ISOCORE 7.5 / **ICI176532714**
MELAN SQUARE WHITE



ISOCORE 7.5 / **ICI176532710**
MELAN SQUARE LIGHT



ISOCORE 7.5 / **ICI176532606**
MYKONOS SQUARE MEDIUM GREY



ISOCORE 7.5 / **ICI176532712**
MELAN SQUARE BEIGE



ISOCORE 7.5 / **ICI176532611**
MYKONOS SQUARE FLAMED

CLICK STONE / CARRE

| | CLICK STONE CARRE ISOCORE 7.5 | CLICK STONE CARRE ISOCORE 8.0 |
|--|---|---|
| KONSTRUKTION / CONSTRUCTION / COSTRUZIONE / CONSTRUCCIÓN | 1.5 MM LVT - 4 MM ISOCORE - 2 MM IXPE PA | 2 MM LVT - 4 MM ISOCORE - 2MM IXPE PA |
| TICKNESS / EPAISSEUR TOTALE / SPESSORE / ESPESOR |  7.5 MM | 8.0 MM |
| NUTZSCHICHT / COUCHE D'USURE / STRATO D'USURA / CAPA DE DESGASTE |  0.55 MM | 0.55 MM |
| STRAPAZIERKLASSE / CLASSE D'USAGE / CLASSE D'UTILIZZO / CLASE DE UTILIZACIÓN |  CLASSE 33 CLASSE 42 | CLASSE 33 CLASSE 42 |
| BESCHICHTUNG / PROTECTION / RIVSTIMENTO / REVESTIMIENTO | PU WITH CERAMIC BEAD - ULTRAFRESH | PU WITH CERAMIC BEAD - ULTRAFRESH |
| STRUKTUR / STRUCTURE / STRUTTURA / RELIEVE | CONCRETE | IRE COIN |
| ABGESCHRÄGT / BISEAUTÉ / BISELLATURA / BISELADO | YES | YES |
| ABMESSUNG DER DIELEN / DIMENSIONS DE LA LAME / DIMENSIONI / TAMAÑO DE LAMA |  605 X 605 MM | 605 X 605 MM |
| KARTONVERPACKUNG / EMBALLAGES EN CARTON / SCATOLE / EMBALAJE DE CARTÓN | 1.83 M ² /PACK 5 TILES | 1.83 M ² /PACK 5 TILES |
| VERPACKUNG AUF PALETTE / BOÎTES PAR PALETTE / NR SCATOLE À PALETTA / EMBALAJE DE PALÉ | 73.2 M ² 40 CARTONS | 73.2 M ² 40 CARTONS |
| NETTO-BRUTTO-GEWICHT PRO PALETTE / POIDS NET-BRUT PAR PALETTE / PESO NETTO - LORDO À PALETTA / PESO BRUTO-NETO POR PALÉ | 540 KG / 550 KG | 630 KG / 640 KG |
| IMPACT SOUND INSULATION / ISOLATION ACOUSTIQUE / ISOLAMENTO ACUSTICO / AISLAMIENTO DE SONIDO DE IMPACTO |  21 DB | 21 DB |
| STUHLROLLENWIDERSTAND / ESSAI DE LA CHAISE À ROULETTES / PROVA CON POLTRONA A ROTELLE / RESISTENCIA A LA RUDA DE LAS SILLAS |  NO DAMAGE | NO DAMAGE |
| EFFEKT VON MÖBELBEINEN / EFFECT DE PIED DE MEUBLE / EFFETTO DI GAMBE MOBILI / EFECTO DE PATA DE MUEBLE |  NO DAMAGE | NO DAMAGE |
| THERMISCHER WIDERSTAND / RÉSISTANCE THERMIQUE / RESISTENZA TERMICA / RESISTENCIA TÉRMICA |  0.0621 M ² K/W | 0.0621 M ² K/W |
| ELEKTROSTATISCHE EIGENSCHAFT / POTENTIEL DE CHARGE ELECTROSTATIQUE / POTENZIALE DI CARICA ELETTRISTATICA / RENDIMIENTO ELECTROSTÁTICO |  -2.0 KV | -2.0 KV |
| VERSCHLEISSBESTÄNDIGKEIT / RÉSISTANCE D'USURE / RESISTANCE ALL'USURA / RESISTENCIA AL DESGASTE |  > 4000 CYCLES | > 4000 CYCLES |
| SCHLAGBESTÄNDIGKEIT / RESISTANCE AUX CHOCS / RESISTENZA ALL'URTO / RESISTENCIA A LOS IMPACTOS |  1450 MM | 1450 MM |
| LOCKING STRENGTH / FORCE DE VERROUILLAGE / FORZA DI BLOCCAGGIO / FUERZA DE BLOQUEO |  LONG SIDE - 3.26 KN/M SHORT SIDE - 6.16 KN/M | LONG SIDE - 3.26 KN/M SHORT SIDE - 6.16 KN/M |
| RESTEINDRUCK / POINÇONNEMENT RÉMANENT / SENSIBILITÀ DI IMPRESSIONE / MARGEN RESIDUAL |  -0.20 MM | -0.20 MM |
| DIMENSIONSSTABILITÄT / STABILITÉ DIMENSIONNELLE / STABILITÀ DIMENSIONALE / ESTABILIDAD DIMENSIONAL |  < 0.25% | < 0.25% |
| BRANDKLASSE / CLASSIFICATION AU FEU / CLASSIFICAZIONE AL FUOCO / CLASIFICACIÓN DE RESISTENCIA AL FUEGO |  BFL-SI BFL | BFL-SI BFL |
| FORMALDEHYD-EMISSION / EMISSION DE FORMALDEHYDE / EMISSIONE DI FORMALDEIDE / EMISIÓN DE FORMALDEHÍDO |  CLASS E1 | CLASS E1 |
| GARANTIE FÜR PRIVATGEBRAUCH / PÉRIODE DE GARANTIE USAGE DOMESTIQUE / GARANZIA PER USO DOMESTICO / GARANTÍA PARA USO DOMÉSTICO | 25 YEARS | 25 YEARS |
| GARANTIE FÜR KOMMERZIELLEN GEBRAUCH / PÉRIODE DE GARANTIE USAGE COMMERCIAL / GARANZIA PER USO COMMERCIALE / GARANTÍA PARA USO COMERCIAL | 10 YEARS | 10 YEARS |

CLICK STONE / XL



ISOCORE 7.5 / IC4442110

ASTRAL STONE LIGHT



ISOCORE 7.5 / IC4442170









ASTRAL STONE DEEP



ISOCORE 7.5 / IC4442100

ASTRAL STONE DARK

CLICK STONE / XL

| | | |
|--|--|---|
| KONSTRUKTION / CONSTRUCTION / COSTRUZIONE / CONSTRUCCIÓN | | CLICK STONE XL ISOCORE 7.5 |
| TICKNESS / EPAISSEUR TOTALE / SPESSORE / ESPESOR | | 2 MM LVT - 4 MM ISOCORE - 1.5 MM IXPE PA |
| NUTZSCHICHT / COUCHE D'USURE / STRATO D'USURA / CAPA DE DESGASTE | |  7.5 MM |
| STRAPAZIERKLASSE / CLASSE D'USAGE / CLASSE D'UTILIZZO / CLASE DE UTILIZACIÓN | |  0.55 MM |
| BESCHICHTUNG / PROTECTION / RIVSTIMENTO / REVESTIMIENTO | |  CLASSE 33 CLASSE 42 |
| STRUKTUR / STRUCTURE / STRUTTURA / RELIEVE | | PU WITH CERAMIC BEAD - ULTRAFRESH |
| ABGESCHRÄGT / BISEAUTÉ / BISELLATURA / BISELADO | | CONCRETE STRUCTURE |
| ABMESSUNG DER DIELEN / DIMENSIONS DE LA LAME / DIMENSIONI / TAMAÑO DE LAMA | | YES |
| KARTONVERPACKUNG / EMBALLAGES EN CARTON / SCATOLE / EMBALAJE DE CARTÓN | |  406.4 X 812.8 MM |
| VERPACKUNG AUF PALETTE / BOÎTES PAR PALETTE / NR SCATOLE A PALETTA / EMBALAJE DE PALÉ | | 1.98 M ² / PACK 6 TILES |
| NETTO-BRUTTO-GEWICHT PRO PALETTE / POIDS NET-BRUT PAR PALETTE / PESO NETTO - LORDO À PALETTA / PESO BRUTO-NETO POR PALÉ | | 89.1 M ² 45 CARTONS |
| TRITTSCHALLDÄMMUNG / ISOLATION ACOUSTIQUE / ISOLAMENTO ACÚSTICO / AISLAMIENTO DE SONIDO DE IMPACTO | | 765 KG / 775 KG |
| STUHLROLLENWIDERSTAND / ESSAI DE LA CHAISE À ROULETTES / PROVA CON POLTRONA A ROTELLE / RESISTENCIA A LA RUDA DE LAS SILLAS | |  21 DB |
| EFFEKT VON MÖBELBEINEN / EFFECT DE PIED DE MEUBLE / EFFETTO DI GAMBE MOBILI / EFECTO DE PATA DE MUEBLE | |  NO DAMAGE |
| THERMISCHER WIDERSTAND / RÉSISTANCE THERMIQUE / RESISTENZA TERMICA / RESISTENCIA TÉRMICA | |  NO DAMAGE |
| ELECTROSTATIC PERFORMANCE / POTENTIEL DE CHARGE ELECTROSTATIQUE / POTENZIALE DI CARICA ELETTROSTATICA / RENDIMIENTO ELECTROSTÁTICO | |  0.0621 M ² K/W |
| VERSCHLEISSBESTÄNDIGKEIT / RÉSISTANCE D'USURE / RESISTANCE ALL'USURA / RESISTENCIA AL DESGASTE | |  > 2.0 KV |
| SCHLAGBESTÄNDIGKEIT / RESISTANCE AUX CHOCS / RESISTENZA ALL'URTO / RESISTENCIA A LOS IMPACTOS | |  > 4000 CYCLES |
| LOCKING STRENGTH / FORCE DE VERROUILLAGE / FORZA DI BLOCCAGGIO / FUERZA DE BLOQUEO | |  1450 MM |
| RESTEINDRUCK / POINÇONNEMENT RÉMANENT / SENSIBILITÀ DI IMPRESSIONE / MARGEN RESIDUAL | |  LONG SIDE - 3.26 KN/M SHORT SIDE - 6.16 KN/M |
| DIMENSIONAL STABILITY / STABILITÉ DIMENSIONNELLE / STABILITÀ DIMENSIONALE / ESTABILIDAD DIMENSIONAL | |  - 0.20 MM |
| BRANDKLASSE / CLASSIFICATION AU FEU / CLASSIFICAZIONE AL FUOCO / CLASIFICACIÓN DE RESISTENCIA AL FUEGO | |  < 0.25 % |
| FORMALDEHYD-EMISSION / EMISSION DE FORMALDEHYDE / EMISSIONE DI FORMALDEIDE / EMISIÓN DE FORMALDEHÍDO | |  BFL-SI |
| GARANTIE FÜR PRIVATGEBRAUCH / PÉRIODE DE GARANTIE USAGE DOMESTIQUE / GARANZIA PER USO DOMESTICO / GARANTÍA PARA USO DOMÉSTICO | |  CLASS E1 |
| GARANTIE FÜR KOMMERZIELLEN GEBRAUCH / PÉRIODE DE GARANTIE USAGE COMMERCIAL / GARANZIA PER USO COMMERCIALE / GARANTÍA PARA USO COMERCIAL | | 25 YEARS |
| | | 10 YEARS |